



CoverSafe
Spark



PROTECT AGAINST ELECTRICAL DANGERS WHEN WORKING IN ATTICS OR IN ROOF AREAS

Designed to **protect against any electrical dangers**, CoverSafe Spark is a lightweight working platform to **prevent workers falling through ceilings** when working in roof spaces. Ideal for all roof and attic operations, open joists or voids up to 2'11" or 900mm.



INNOVATIVE PATENTED SAFETY SOLUTIONS

INSULATED SAFETY MATTING



KEY FEATURES & BENEFITS

- Prevents shocks from faulty or broken electrical fittings or old wiring
- Easy to install & adaptable - can be expanded to many sizes
- Protects against falls through ceilings

The CoverSafe Spark mat is constructed with Glass Reinforced Plastic, meaning it is insulated and will protect against any electrical dangers. When working in roof spaces you'll be protected from possible shocks from old or faulty wiring, possibly hidden in the thermal insulation. GRP material was developed for aerospace and Formula One racing, and has been woven into the CoverSafe Spark's design to provide an innovative temporary work platform that is lightweight but extremely durable.

The CoverSafe Spark mat is highly adaptable and can be expanded to a variety of sizes depending on the need of the job. The closed-up mat is easy to transport and install, XSpan technology means it can even fit through small attic hatches and access points, then be expanded to suit the space being protected. The mat comes with its own bag to assist with the transportation and carrying of additional tools.

Canada

- CSA S269.2-16 (reaffirmed 2021) Access scaffolding for construction purposes
- 6.2.3 Live loads on access scaffold platforms – OSC matting products comply with all three loading duties
- CSA Z797:18 National Standard of Canada (reaffirmed 2023)
- Code of practice for access scaffold – OSC matting products comply with all three loading duties

SPECIFICATION

COVERSAFE SPARK

Open size	6'6" x 2'7", covers 17'2" sq. ft. 2m x 0.8m, covers 1.6m ²
Closed size	3'9" x 1'7" 1.15m x 0.48m
Weight	20.28 lbs 9.2kg
Maximum working load	330.70 lbs 150kg

COVERSAFE SPARK MINI

Open size	2'3" x 3'11", covers 8'7" sq. ft. 0.7m x 1.20m, covers 0.8m ²
Closed size	2'11" x 1'1" 0.9m x 0.32m
Weight	10.14 lbs 4.6kg
Maximum working load	330.70 lbs 150kg

CURRENTLY USED IN THESE SECTORS



Head Office Ontario
40 North Rivermede Road,
Units 6 - 7 Concord,
Ontario L4K 2H3

Regional Office
Alberta Office & Training Centre
Unit 107 – 7155, 57 Street SE Calgary,
Alberta T2C 5B1
Québec Office
118 - 6185 boul. Taschereau
local 180 Brossard, Québec J4Z 0E4

Tel: (905) 669 1494
Toll Free: (877) 505 5003
Web: www.keesafety.ca